A02B-0047-C062

FANUC Corporation · FANUC System 3/5/6 CNC

FEATURES

Bubble tape reader (BTR) unit for FANUC System 3/5/6 CNC, without a reel take-up.

Hardware

Function:
paper-tape reader / BTR unit (supplier-reported multi-source consensus: DNC Electronics, eBay, FanucWorld, MRO Electric, DO Supply, yorkmro)

Reel:
without reel (supplier-reported; FanucWorld + eBay listings)

Communication

Electrical

Electrical:
Not applicable (passive component; powered by host system)

Supply voltage:
Not applicable

Environmental

Operating ambient temperature:
0 to 55 °C (family-level reference; not confirmed for this specific order code; per B-61393E p.112 for Series 0/00/0-Mate)

www.autronexa.com

Storage/transport ambient temperature:
−20 to 60 °C (family-level reference; not confirmed for this specific order code; per B-61393E p.112)

Relative humidity:
75%RH or less, no condensation

Physical

Dimensions (H×W×D):
Not published as numerical table (BTR tape reader unit)

Weight:
~1.50 kg (supplier-reported; typical FANUC BTR unit family)

Lifecycle

Legacy (spare part for early FANUC CNC generations; listed in aftermarket channels) (Last verified: 2026-09)