A02B-0047-C310

FANUC Corporation · FANUC System 3/5/6 CNC

FEATURES

Operator control panel with 7-segment LED indicators for early FANUC CNC (aftermarket listings reference Ikegai FX applications).

Hardware

Indicators:
7-segment LED displays (multi-source consensus; supplier-reported)

Layout:
operator control panel (multi-source consensus; supplier-reported)

Communication

Electrical

Supply voltage:
Not published by manufacturer (early CRT/MDI unit; no published spec located for this order code)

Power consumption:
25 W (supplier-reported single source; DO Supply product page)

Environmental

Operating ambient temperature:
0 to 55 °C (family-level reference; not confirmed for this specific order code; per B-61393E p.112 for Series 0/00/0-Mate)

www.autronexa.com

Storage/transport ambient temperature:
−20 to 60 °C (family-level reference; not confirmed for this specific order code; per B-61393E p.112)

Relative humidity:
75%RH or less, no condensation

Physical

Dimensions (H×W×D):
Not published by manufacturer (early CRT/MDI unit; no published spec located for this order code)

Weight:
Not published by manufacturer (early CRT/MDI unit; no published spec located for this order code)

Lifecycle

Legacy (early FANUC CNC generation; superseded by i-series / 30i-B generation; no official EOS date verified) (Last verified:
2026-09)