A02B-0050-C553

FANUC Corporation · FANUC CNC accessory (order code family A02B-0050)

FEATURES

MDI/CRT option unit incorporating a manual pulse generator (MPG) interface (aftermarket listings reference A860-0201-T001 pulse generator).

Hardware

Function:
MDI/CRT option unit with manual pulse generator interface (multi-source consensus; supplier-reported)

MPG interface:
A860-0201-T001 pulse generator support (multi-source consensus; supplier-reported)

Communication

Electrical

Electrical:
Not applicable (passive component; powered by host system)

Supply voltage:
Not applicable

Environmental

Operating temperature:
0 to 55 °C (family-level reference; not confirmed for this specific order code; per GFZ-63523EN/03 p.233)

Storage temperature:
-20 to 60 °C (family-level reference; not confirmed for this specific order code; per GFZ-63523EN/03 p.233)

www.autronexa.com

Relative humidity:
75%RH or less, no condensation (family-level reference; cross-generation manual not confirmed for this specific order code (per GFZ-63523EN/03)

Physical

Dimensions (H×W×D):
29 × 69 × 115 mm (multi-source consensus; supplier-reported; typical FANUC MPG form factor)

Weight:
~0.3 kg (manual-cited; FANUC A-45344 portable MPG spec, excl. cable; ~0.85 kg with coiled cable)

Lifecycle

Legacy (early FANUC CNC generation; superseded by i-series / 30i-B generation; no official EOS date verified) (Last verified:
2026-09)