B&R 8KSJ Series Service Manual

8KSJ82.ee010ff00-h

1. Description

8KSJ high-torque three-phase synchronous servo motor (8KS series). Permanent-magnet synchronous motor with optimized external ventilation or liquid cooling for very high torque and power density, high efficiency and high dynamics. Ideal for the most demanding applications in general machine manufacturing, supported by a high overload capacity. Robust and compact, virtually maintenance-free. Features: nominal power up to 140 kW, air-cooled or water-cooled variants, encoders for functional safety, high dynamic torque at high speeds.

2. Technical Parameters

Parameter	Value
Nominal speed nN [rpm]	1000
Number of pole pairs	3
Nominal torque Mn [Nm]	175
Nominal power PN [W]	18326
Nominal current IN [A]	39.1
Stall torque M0 [Nm]	180
Stall current I0 [A]	40.4
Maximum torque Mmax [Nm]	340
Maximum current Imax [A]	85
Maximum speed nmax [rpm]	4300
Torque constant KT [Nm/A]	4.65
Voltage constant KE [V/1000rpm]	296
Stator resistance R2ph [Ohm]	0.64
Stator inductance L2ph [mH]	19.4
Electrical time constant tel [ms]	31.656
Thermal time constant ttherm [min]	16.1
Moment of inertia J [kg·cm2]	450
Mass m (without brake) [kg]	110
Holding torque of brake MBr [Nm]	200
Brake mass [kg]	13
Moment of inertia of brake JBr [kg·cm2]	40
Cable cross-section [mm2]	10
Connector size/type	Terminal box
Recommended servo drive (ACOPOS)	0660

www.autronexa.com

3. Product Information

Order number: 8KSJ82.ee010ff00-h

Additional information from the manufacturer's manual:

Compliance: UL/C-UR-US listed, UL file E480221 (cooling type J); standards EN 60034-1/5/6/7/11/14; class 3K3/3Z12. Life-cycle status not stated in the manual.

Rating & cooling: EN 60034-1 S1 continuous; insulation class F; cooling liquid-cooled with integrated heat exchanger, IC 3W7 (incoming coolant 10-25 degC, max. 5 K below ambient); thermal protection KTY84-130, max winding 155 degC.

Mounting per EN 60034-7: horizontal IM B5 or IM B35. FF flange per IEC; shaft end DIN 748; key DIN 6885-1 Form A; balancing DIN ISO 8821; runout DIN 42955 N; coating water-based RAL 9005; bearing life LH10 20,000 h.

Environment: class 3K3/3Z12 at 0..+40 degC (= -15..+60 degC), rel. humidity 5-85%; max. elevation 1000 m; IP54; vibration resistance radial 3 g / axial 1 g (10-55 Hz).

Shaft loads: permissible radial force per model (Fr vs speed diagrams); reinforced A-side bearing option. Noise: no motor-body sound level; liquid cooling significantly reduces noise emissions vs fan-cooled variants.

Feedback: resolver, EnDat 2.1 (ECN 1313/EQN 1325) or EnDat 2.2; encoders for functional safety available. Power via terminal box; encoder via speedtec or ITEC.

Safety: encoders support functional safety; STO implemented by ACOPOS servo drive.